



Maxx Fiber

polypropylene fiber



ISO 9001:2015



Smart Cities & Green Building Concept in India



Maxx Fiber

Polypropylene fiber

Description

Maxx PP Fiber (6mm/12mm) is a high-performance monofilament polypropylene Fiber developed as a crack controlling additive for concrete and mortar. It is supplied ready for use, and in measured quantities for addition to the concrete mix whether at the batching plant or on site.

Technical Data

Colour	White
Alkali content	Nil
Sulphate content	Nil
Air entrainment	Air content of concrete will not be significantly increased
Chloride content	Nil
Fibre diameter	24 – 44 microns
Fibre length	6mm/12mm
Estimated usage	125 gm for 50 kg cement bag
Anticipated tensile strength	≤ 350MPa

Specification

Maxx PP fiber is used to inhibit the formation of small cracks which can occur through plastic shrinkage and settlement, premature drying and early thermal changes, in order to provide utilisation of the intrinsic properties of the hardened cementitious material. Specifically designed for crack control in cementitious materials covering areas such as ready -mix concrete, precast concrete, conventional shotcrete, screeds rendering mortars, etc. Principle uses of fibre concrete include: concrete slabs, pavements, driveways, imprinted concrete, curbs, pipes, overlays patch repair, micro-silica concrete, thin section walling, water retaining structures, marine concrete, heavy industrial floors etc.

Benefits

- Good substitute for wire mesh in factory and warehouse floors.
- Inhibits intrinsic cracking in concrete.
- Disperses uniformly throughout the mix if done properly.
- Improves finishing characteristics.
- Improves concrete durability.
- Increases impact and abrasion resistance.
- Rustproof.
- Impervious to alkali attack.
- Helps retain moisture for better curing.
- Reduced risk of subsequent damage.
- Improves fire resistance – reduces the incidence of explosive spalling during heating.

Application Method

For Onsite Machine Mixing

Small quantity of water is dosed in empty drum to clean the drum after each batch. Add fibre in the rotating drum. Then add chips/ sand/ cement/ water in the concrete mixer and continue normal operation.

For Dosing in Ready Mix Truck – Add fibres in small lots in the rotating drum. After dosing is complete allow extra 20 – 30 revolutions of drum at maximum RPM.

For Manual Mixing – Put fibres in a bucket of water and stir it so that fibres disperse in water. Spread the water and fibre mixture on the dry cementitious mix.

Compatibility

Can be used with all types of cement and is compatible with other admixtures.

Storage

Should be stored in dry conditions.

Packaging

Maxx Fibre 6mm/12mm is available in 90 & 125 gm pouch.

GLOBE CONSTRUCTION CHEMICALS

An ISO 9001 : 2015 Company

HISS No. 219, S.No. 55/2/2, Behind Prayaja City, Vadgaon Khurd, Pune – 411051

MOB : CC - +91 8888323846, Mail Id globechemicALS055@GMAIL.Com