



MAXX WHITE PRIME

Interior and exterior surface primer



ISO 9001:2015



Indian Green Building Council
Greening India since 2007
Smart Cities & Green Building Concept in India

MAXX WHITE PRIME

Interior & Exterior Surface Primer

Product Description

Maxx White Prime is an emulsion based water thinnable primer that is specially designed for application on the exterior as well interior masonry surfaces. It can also be applied to a wide range of cement plasters, ceiling , asbestos sheets, concrete etc.

Features and Benefits

- Interior & Exterior application
- Can be used for priming walls, bricks work, concrete etc
- Excellent drying time
- Smooth finish

Direction For Use

Surface Preparation

- Sand the surface with emery paper no. 180 to remove loose particles, paints, dust, cracked and flaking paint and wipe clean.
- Surface should be free from any loose paint, dust or grease . Growth of fungus, algae or moss should be removed by wire brushing and water.
- For concrete and plaster wash surface with water under high pressure let dry and apply one thin coat of Maxx White Prime.
- If there cracks on surface fill the cracks with crack filler.

Application

Primer :

Apply a coat of Maxx White Prime by thinning with water in the ratio of 1:1 by volume and allow drying for 6 – 8 hours.

Putty :

Smoothen the surface by filling dents with a thin coat of Xtra white wall putty and allow drying for 4 -6 hours. Sand the surface with emery paper no.180 and wipe clean.

Primer :

Apply another coat of Maxx White Prime and allow drying for 5 – 8 hours. Before application of topcoat, sand the surface with emery paper no.320 and wipe clean.

Precaution

- Do not apply when ambient temperature is less than 10 c or if the temperature might drop to this level within 4 hrs of application.
- Do not over thin or over extend the brush.

Technical Properties

Specific gravity	1.4
Finish	Matt and smooth
Coverage	80 - 100 sq.ft/ 1 coat
Drying time	30 min to 1 hour depending on weather condition
Packaging	1 lit, 5 lit, 10 lit, 20 lit
Shelf Life	2 Years from date of manufacturing

Safety Features

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting
- In case of contact with eyes wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty container to store foods.

GLOBE CONSTRUCTION CHEMICAL PVT LTD.

An ISO 9001 : 2015 Company

HISS No. 219, S.No. 55/2/2, Behind Prayeja City, Vadgaon Khurd, Pune – 411051

MOB : CC - +91 8888323846, Mail Id: info@globechem.in